

SAFETY  
FIRST



**HAEMATOKRIT 210**  
Special-purpose Centrifuge

At 16,060 g sedimentation is completed in just a little over 6 minutes.

At any rate, a run time of 10 minutes is sufficient. The rotor comes to a braked standstill.

Each capillary is secured within its own chamber and supported by a holding tray. This holding tray serves to contain glass shards and any leakage should a tube break. It is easy to clean and disposable in the case of glass breakage.

Capillaries, to be used for quantitative buffy coat analysis are centrifuged in the 20-place rotor prior to further analysis.

HAEMATOKRIT 210 control panel



## USER-FRIENDLINESS

- Quick-entry keypad
  - Easy-to-read, digital display
  - Display of current parameter values
- Easy entry of the parameters
  - RPM in increments of 100
  - Running time in minutes, max. 99 min

## SAFETY

- Lid locking and holding
- Emergency lid lock release
- Motor overheating protection
- Imbalance switch-off
- Standstill indication



Cat. No.	2076
----------	------

capillaries per rotor	24		
capillaries	basic	mylar-coated	self-sealing and mylar-coated
Cat. No.	2074	1072	1071

sealing putty	
Cat. No.	2077



The holding trays are easy to clean and are disposable in the case of glass breakage.



rotor, 20-place  
for capillaries for quantitative Buffy Coat Analysis, with lid (not suited for standard capillaries).

Cat. No. 2058

## TECHNOLOGY

### HAEMATOKRIT 210

Hematocrit centrifuge, without rotor		
Power supply *	208 – 240 V 1~	100 – 127 V 1~
Frequency	50 – 60 Hz	
Consumption	300 VA	220 VA
Radio interference	EN 55011 ISM class B	FCC class B
Immunity	EN 50082-1	-

Max. capacity	24/20 capillaries
Max. RPM (speed)	13,000 min <sup>-1</sup>
Max. RCF	16,060

Dimensions (H x W x D) in mm	247 x 275 x 330
Weight	approx. 10 kg

Cat. No.	2104	2104 – 01
----------	------	-----------

## C&M SCIENTIFIC

Unit 4, Lindsay Square, Deans Industrial Estate,  
Livingston, West Lothian, EH54 8RL

Tel: 08452 608 601 Fax: 08452 608 602

[www.cmscientific.co.uk](http://www.cmscientific.co.uk)

