

Nano SPY T3

Mini Extreme Temperature Data logger 2,4GHz radiofrequency communication



Non contractual photo

Presentation

The Nano SPY T3 measures and records temperature with its external probe. It transmits the data to a nearby LINK module via 2.4 GHz radio frequency communication.

The data are then automatically sent to the JRI secure Cloud for hosting, and will be managed from JRI MySirius web application.

If thresholds are exceeded, alerts are transmitted in real time to react immediately.

Designed to monitor thermo-controlled chambers, the sensor can be fixed thanks to its magnet outside the equipment.

Technical features

	Low T°C Version	High T°C Version
Interface	Status LED and On/Off touch sensitve button	
Measurement range	-200°C to 0°C	0°C to +260°C
Accuracy	$\pm 0.2^{\circ}$ C from -20° C to 0° C $\pm 0.5^{\circ}$ C out of this range	$\pm 0.3^{\circ}$ C from 0°C to $\pm 100^{\circ}$ C $\pm 0.5^{\circ}$ C out of this range
Communication frequency	2,4 GHz (802.15.4)	
Memory	10 000 data points	
Sensor	External stainless steel PT100 - Ø2,9x25mm	
Operating conditions	-20°C to +50°C	
Resolution	0.01	
Measuring and transmission period	Adjustable from 5 sec to 12hrs	
Internal memory recording period	Adjustable from 5 sec to 24 hrs	
Response time σ_{90}	~ 2mn	
Protection	IP65	
Case	Polycarbonate – Food contact	
Power supply	Lithium 3,6v battery - Replaceable	
Battery life	2 to 4 years depending on use	
Dimensions and weight	63 x 42 x 25 mm / ~ 60 g	
Cable lenght	50 cm or 3m	3m
Fixation	Fixing eyelets and integrated magnets	
Supplied with	Battery, red identification ring User manual can be download on www.jri-maxant.com	
Compliance	CE, ROHS, FCC, ETS 300-328, EN 12830	
Standard calibration points	-80°C/+5°C	+20°C/+100°C

JRI, Société par actions simplifiée au capital de 4 000 000 €

Pôle logistique / 2 Rue de la Voivre / PA Technoland / BP 21 / 25490 FESCHES LE CHÂTEL / France SIRET 380 332 858 00030 - Tél : +33 (0)3 8130 68 04 / Fax : +33 (0)3 8130 60 99 / sales@jri.fr

Benefits

Easy-to-use

The sensor is ready to use and has operating and alarm lights



Excellent measurement accuracy



Fixing eyelets



Replaceable battery and non disconnectable probe

ART NRS

11693 : Nano SPYT3 3m (High T°C) 11572 : Nano SPYT3 50cm (Low T°C) 11573 : Nano SPYT3 3m (Low T°C)

www.jri-maxant.com